US010551880B1

(12) **United States Patent**
Ai et al.

(10) **Patent No.: US 10,551,880 B1**
(45) **Date of Patent: Feb. 4, 2020**

(54) **ELECTRONIC DEVICES WITH FLEXIBLE DISPLAYS AND HINGES**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Jiang Ai**, Cupertino, CA (US); **Mitchell A. Heschke**, Paso Robles, CA (US); **Soyoung Kim**, San Jose, CA (US); **Stephen R. McClure**, San Francisco, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 296 days.

(21) Appl. No.: **15/232,505**

(22) Filed: **Aug. 9, 2016**

Related U.S. Application Data

(60) Provisional application No. 62/217,219, filed on Sep. 11, 2015, provisional application No. 62/338,827, filed on May 19, 2016.

(51) **Int. Cl.**
G06F 1/16 (2006.01)

(52) **U.S. Cl.**
CPC ***G06F 1/1681*** (2013.01); ***G06F 1/1652*** (2013.01); *G06F 1/1618* (2013.01)

(58) **Field of Classification Search**
CPC G06F 1/1616; G06F 1/1618; G06F 1/1681; G06F 1/1652; E05D 5/02; E05D 5/04; E05D 5/06; E05D 5/08; E05D 5/10; E05D 3/122
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,204,565 B1 12/2015 Lee et al.
9,348,450 B1 * 5/2016 Kim G06F 1/1681
9,541,962 B2 1/2017 Siddiqui
9,544,993 B2 1/2017 Lee et al.
2011/0150453 A1 * 6/2011 Chang G03B 35/08 396/326
2012/0307423 A1 * 12/2012 Bohn G06F 1/1641 361/679.01
2012/0307472 A1 12/2012 Bohn et al.
2013/0243608 A1 * 9/2013 Sakamoto F04B 49/22 417/26
2013/0342090 A1 * 12/2013 Ahn G09F 9/33 312/258
2013/0342094 A1 * 12/2013 Walters G09F 19/00 312/319.2

(Continued)

OTHER PUBLICATIONS

Stic Search (Year: 2019).*

Primary Examiner — Steven T Sawyer
Assistant Examiner — Sagar Shrestha
(74) *Attorney, Agent, or Firm* — Treyz Law Group, P.C.; G. Victor Treyz; Kendall W. Abbasi

(57) **ABSTRACT**

An electronic device may have a flexible display that overlaps an axis. The display may be supported by a housing. The housing may have first and second portions that rotate relative to each other about the axis. The housing may be placed in an unfolded configuration to support the display in a planar state. The housing may also be placed in a folded configuration by rotating the first and second portions relative to each other. A hinge mechanism may be used to ensure adequate separation between the first and second portions when the housing is bent. Movable flaps may be retracted when the housing is bent to create room for a bent portion of the display.

28 Claims, 37 Drawing Sheets